

**RP5 RUNPOTEC Polyester Ø 5,5 mm – without meter counter**

optimal for pipe diameter 16–40 mm

Item no.: **10013** | **10014**

**VIDEO**

RP5

Click here Video

**KG 270**

**PATENTED**

Click here Productinformation

**Beginning:**  
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Glide back protection  
Active (Only stops RG7 Guiding head)

Triple twisted special polyester fish tape Ø 5,5 mm

**Ending:**  
RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

**Attention!**  
electric conductive

Very narrow bending radius

**R = 15 mm**

Virtually break-free even with tightest radii

**R**

50 % less friction resistance

Only punctual contact

Total breaking load 270 kg

Strand + Pressing + Guiding head + Eyelet

**KG 270**

Rod	Rec. pipe-ID Ø	Bending radius	Total breaking load incl. RG7 - RUNPOGLIDER
Ø			
5,5 mm	9 – 32 mm	15 mm	270 kg

**DATA**

ITEM NO.	10013	10014
LENGTH	20 m	30 m
WEIGHT	1,31 kg	1,62 kg
EAN-CODE	9120045472806	9120045472813
DIMENSION BOX	L 380 X W 310 X H 50 mm	
TOTAL BREAKING LOAD	270 kg (on the whole strap)	
ROD Ø	Ø 5,5 mm	
MATERIAL	triple twisted special polyester fish tape	
BENDING RADIUS	15 m	
PIPE INNER Ø	optimally from 9 mm - 32 mm	

**DESCRIPTION**

The RP5 - RUNPOTEC Polyester Ø 5.5 mm is a cable pulling tool without a meter counter. The triple-twisted special plastic tape with a diameter of 5.5 mm has an even better shearing effect than the 3 mm fiberglass rod; the frictional resistance is only half the normal value due to spot contact. The patented RG7 guiding head with swivel Ø 5.5 mm (pressed at the beginning and end of the tape) allows overcoming tight radii (bending radius 15 mm). The RP5 - RUNPOTEC Polyester Ø 5.5 mm is stored in a jobsite suitable and robust storage box with an ergonomic carrying handle. It is equipped with the new glide back protection (only stops the RG7 guiding head), which prevents the cable pulling strap from slipping back accidentally. The incredible total breaking load of 270 kg refers to the entire pulling system. Labour- and time-consuming repair work is no longer necessary, as this cable pulling system is virtually breakage-free.

**Optimal field of application:** for pipe inner diameter 9 - 32 mm

**Scope of supply:** 1 x RP5 cable pulling tape Ø 5,5 mm without meter counter in a plastic box, length: 20 m, including 2 x RG7 RUNPOGLIDER with swivel (pressed on both sides)

**ADVANTAGES**

- Total breaking load 270 kg
- 2 x RG7 - Guiding head with swivel Ø 7 mm
- Glide back protection (only stops the RG7 Guiding head)
- Triple twisted special plastic tape Ø 5,5 mm
- 50 % less frictional resistance
- Virtually break-free, even with the tightest radii

**INFORMATION****Compatible accessories:****RP5 Replacement fish tape**

20 m – Item no.: 20240

30 m – Item no.: 20241

**Cable pulling loop with hook**

(Quick release fastener) – set of 4

Item no.: 10159