

EPD Duct Rod on Reel (Cobra)

High quality glass fibre reinforced helically wound epoxy rod giving good adhesion properties for the outer polyethylene coating. This construction gives excellent bending elasticity and is an ideal and fast way of installing draw ropes, winch ropes and lightweight cables into ducts, ready for cable pulling operations.

Rod supplied complete with end connectors and guide tip. A Full range of accessories is also available.

Also available as a Rod only

Rod Material: Glass fibre and high quality resin. The exterior layer is covered with high density UV resistant polyethylene.

Rod colour: Yellow

Frame Material: Zinc Plated

**Free Standing Mini Duct Rod
(4mm & 6mm)**



**Mobile Duct Rod
(9mm, 11mm & 14mm)**



Specification:

	SKU:	102-51	102-61	102-71	102-81	102-91
Rod Diameter	(mm)	4	6	9	11	14
Dimensions (L x H x W)	(mm)	405 x 470 x 190	530 x 580 x 247	921 x 1015 x 460	1048 x 1150 x 520	1264 x 1282 x 520
Inside Wheel Diameter Ø	(mm)	393	514	901	1028	1240
Frame Type	-	Free Standing	Free Standing	Mobile	Mobile	Mobile
Maximum Length of Push or Pull	(m)	100	150	200	350	500