



PRODUCT SPECIFICATION & TECHNICAL DATA

FP74 - Single 140kg 1.8m Lanyard with Shock Absorber

Collection: Lanyards

Range: Height Safety

Materials: Polyester Webbing, Alloy Steel, Heat Treated, Zinc

Outer Carton: 10

Product information

This single ended lanyard features a shock absorber, a scaffold hook and a snap hook. It is tested to withstand a 140KG user and is 180cm long including connectors when fully extended.



Lanyards

The Portwest collection of lanyards are for restraint, positioning and fall arrest systems. Available in different lengths and material types including rope, webbing and elasticated webbing for ultimate wearer choice.

Height Safety

Height Safety is put in place to prevent the risks associated with falling from heights, reducing impact force, restricting obstacle/ground collision and restricting users from fall hazard areas. Portwest offer a full range of Height Safety products for working at height.

Standards

EN 354:2010
EN 355:2002 (140KG)
EN 362:2004



Features

- Elasticated webbing reduces the risk of tripping or snagging
- Shock Absorbing
- 52mm scaffolding hook opening
- Durable webbing with high breaking strength
- Max rated load 140kg
- 10 Year shelf life from manufacturing date outlined in product label
- CE certified
- UKCA marked
- Retail box which aids presentation for retail sales



PRODUCT SPECIFICATION & TECHNICAL DATA

FP74 - Single 140kg 1.8m Lanyard with Shock Absorber **Commodity Code: 5609000000**

Test House

CCQS Certification Services Ltd. (Notified Body No.: 2834)
Block 1, Blanchardstown Corporate Park
D15 AKK1, Ireland
Cert No: CE-PC-191210-016-04-9C

CARTON DIMENSIONS/WEIGHT

| Item | Colour | Len | Wid | Hgt | Weight (Kg) | Cubic (m ³) | EAN13 | DUN14 |
|---------|--------------|------|------|------|-------------|-------------------------|-------|-------|
| FP74K1R | Black/Orange | 60.0 | 27.0 | 39.0 | 1.7810 | 0.0632 | | |

